



Universal Solar

PV Module WXS300P7-US



Specifications

Cell Type	Multi-Crystalline Silicon
Cell Size	156mmx156mm (6.14x6.14in)
No. of cells and connections	72 (6x12)
Dimension of module(mm)	1956x992x38mm (77.01x39.06x1.50in)
Weight	22.0Kg (48.5lbs)
Power Tolerance	+/- 3%

Electrical Characteristics

Model	WXS300P7-US
Maximum power at STC(Pm)	300W
PTC	274.94W
Open-circuit voltage(Voc)	45.05V
Short-circuit current(Isc)	8.66A
Voltage at Pmax(Vmp)	36.45V
Current at Pmax(Imp)	8.23A
STC: Irradiance 1000W/m ² , 25°C, AM1.5	PTC: Irradiance 1000W/m ² , 20°C, 1m/s windspeed

Limits

Fuse rating	15A
Maximum system voltage	1000VDC (IEC)
Operating temperature	-40°F to +185°F (-40°C to +85°C)

Temperature and Coefficients

NOCT	45°C +/- 2°C
Temp coefficient of Voc	-.313% (± 5%)
Temp coefficient of Isc	.046% (± 5%)
Temp coefficient of power	-.40% (± 5%)


NOCT: Nominal Operation Cell Temperature

Output

Type of output terminal	IP65 Junction Box
Cable	12AWG PV Wire
Cable lengths	1200mm (47.24in)
Connector	MC4

Warranty

Workmanship and Materials	5 Years
90% Power	10 Years
80% Power	25 Years



Mechanical Characteristics

